

# CNS 50 Trend UK

CONVECTOR HEATERS

PRODUCT-NO.: 236559

**CNS 50 Trend UK wall convector – because heating should not be a question of space.**

Sometimes there's just not much room – even for heater. This is why the CNS 50 Trend UK wall convector is very slender. At only 10 cm deep, it nevertheless generates excellent levels of thermal comfort. The CNS 50 Trend UK blends ever so discreetly into its surroundings, efficiently delivering cosy warmth. The comfort functions of the integral controller, such as the 7-day timer, frost protection and open window detection, highlight the efficiency and high quality features of the wall convector.



## The main features

Wall mounted convector – ideal as a booster heater or interim heater for spring/autumn

500 W heating output

Even, quiet room air heating

Metal casing and slimline design

Controls with backlit LCD

7-day timer, frost protection and open window detection

Control unit with self-learning capability: Automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection



Type	CNS 50 Trend UK	CNS 75 Trend UK	CNS 100 Trend UK
<b>Part no.</b>	236559	236560	236561

#### Heating output

<b>Rated heating output <math>P_{nom}</math></b>	0,5 kW	0,75 kW	1 kW
<b>Minimum heat output (standard value) <math>P_{min}</math></b>	0 kW	0 kW	0 kW
<b>Maximum continuous heating output <math>P_{max,c}</math></b>	0,5 kW	0,75 kW	1 kW

#### Auxiliary power consumption


<b>D heating output <math>e_{l_{max}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Heat output <math>e_{l_{min}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Dby mode <math>e_{l_{SB}}</math></b>	0,000 kW	0,000 kW	0,000 kW

#### Type of heating output/room temperature control

<b>Single stage heating output, no room temperature control</b>	-	-	-
<b>Two or more manually adjustable stages, no room temperature control</b>	-	-	-
<b>Room temperature control with mechanical thermostat</b>	-	-	-
<b>With electronic room temperature control</b>	-	-	-
<b>Electronic room temperature control and time of day control</b>	-	-	-
<b>Electronic room temperature control and day of week control</b>	x	x	x

#### Other control options

<b>Room temperature control with occupancy detection</b>	-	-	-
<b>Room temperature control with open window detection</b>	x	x	x
<b>With remote control option</b>	-	-	-
<b>With adaptive control for start of heating</b>	x	x	x
<b>With restricted operating times</b>	-	-	-
<b>With black bulb sensor</b>	-	-	-



Type	CNS 150 Trend UK	CNS 200 Trend UK	CNS 250 Trend UK
<b>Part no.</b>	236562	236563	236564

### Heating output

<b>Rated heating output <math>P_{nom}</math></b>	1,5 kW	2 kW	2,5 kW
<b>Minimum heat output (standard value) <math>P_{min}</math></b>	0 kW	0 kW	0 kW
<b>Maximum continuous heating output <math>P_{max,c}</math></b>	1,5 kW	2 kW	2,5 kW

### Auxiliary power consumption

<b>D heating output <math>e_{l_{max}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Heat output <math>e_{l_{min}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Dby mode <math>e_{l_{SB}}</math></b>	0,000 kW	0,000 kW	0,000 kW

### Type of heating output/room temperature control

<b>Single stage heating output, no room temperature control</b>	-	-	-
<b>Two or more manually adjustable stages, no room temperature control</b>	-	-	-
<b>Room temperature control with mechanical thermostat</b>	-	-	-
<b>With electronic room temperature control</b>	-	-	-
<b>Electronic room temperature control and time of day control</b>	-	-	-
<b>Electronic room temperature control and day of week control</b>	x	x	x

### Other control options

<b>Room temperature control with occupancy detection</b>	-	-	-
<b>Room temperature control with open window detection</b>	x	x	x
<b>With remote control option</b>	-	-	-
<b>With adaptive control for start of heating</b>	x	x	x
<b>With restricted operating times</b>	-	-	-
<b>With black bulb sensor</b>	-	-	-



Type	CNS 300 Trend UK
Part no.	236565

#### Heating output

Rated heating output $P_{nom}$	3 kW
Minimum heat output (standard value) $P_{min}$	0 kW
Maximum continuous heating output $P_{max,c}$	3 kW

#### Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW

#### Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	x

#### Other control options

Room temperature control with occupancy detection	-
Room temperature control with open window detection	x
With remote control option	-
With adaptive control for start of heating	x
With restricted operating times	-
With black bulb sensor	-

Depth including 22 mm wall retainer

**Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.